

Philips V Line 241V8L/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Nero

Marchio : Philips Famiglia del prodotto: V Line Codice prodotto: 241V8L/00

Nome del prodotto : 241V8L/00

Monitor 241V8L Monitor LCD

Philips V Line 241V8L/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Nero:

Il monitor Philips V-Line con ampio angolo di visualizzazione offre una visione oltre ogni limite, una qualità elevata e funzioni essenziali. La sincronizzazione adattiva assicura una visualizzazione video fluida. Caratteristiche quali antiriflesso, modalità LowBlue e immagini prive di sfarfallio non affaticano gli occhi.

Philips V Line 241V8L/00. Dimensioni diagonale schermo: 60,5 cm (23.8"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Superficie display: Opaco, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Montaggio standard VESA. Colore del prodotto: Nero



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display resolution *	1920 x 1080 pixels		
HD type *	Full HD		
Native aspect ratio *	16:9		
Display technology *	LCD		
Panel type *	VA	Number of OSD languages	21
Backlight type	W-LED	Plug and Play	✓
Touchscreen *	✗	LED indicators	Operation, Stand-by
Display brightness (typical)	250 cd/m²	Power	
Response time *	4 ms	Energy efficiency class (SDR) *	E
Display surface	Matt	Energy consumption (SDR) per 1000 hours *	18 kWh
Anti-glare screen	✓	Power consumption (typical) *	20.4 W
Screen shape *	Flat	Power consumption (standby) *	0.5 W
Aspect ratio	16:9	Power consumption (off)	0.3 W
Contrast ratio (typical) *	3000:1	AC input voltage	100 - 240 V
Maximum refresh rate *	75 Hz	AC input frequency	50 - 60 Hz
Viewing angle, horizontal	178°	Power supply type	Internal
Viewing angle, vertical	178°	European Product Registry for Energy Labelling (EPREL) code	400127
Display number of colours *	16.7 million colours	Operational conditions	
Pixel pitch	0.2745 x 0.2745 mm	Operating temperature (T-T)	0 - 40 °C
Pixel density	93 ppi	Storage temperature (T-T)	-20 - 60 °C
Horizontal scan range	30 - 85 kHz	Operating relative humidity (H-H)	20 - 80%
Vertical scan range	48 - 75 Hz	Operating altitude	0 - 3658 m
Viewable size, horizontal	52.7 cm	Non-operating altitude	0 - 12192 m
Viewable size, vertical	29.6 cm	Weight & dimensions	
Digital horizontal frequency	30 - 85 kHz	Width (with stand)	540 mm
Display diagonal (metric)	60.5 cm	Depth (with stand)	220 mm
DDC/CI	✓	Height (with stand)	416 mm
Haze rate	25%	Weight (with stand)	3.03 kg
Surface hardness	3H	Width (without stand)	540 mm
Display sRGB	✓		

Performance		Weight & dimensions	
NVIDIA G-SYNC *	✗	Depth (without stand)	51 mm
AMD FreeSync *	✗	Height (without stand)	322 mm
VESA Adaptive Sync support	✓	Weight (without stand)	2.64 kg
Component video sync	Separate sync, Sync-on-green (SOG)	Packaging data	
Flicker-free technology	✓	Package width	608 mm
Low Blue Light technology	✓	Package depth	121 mm
		Package height	415 mm
Multimedia		Package weight	4.25 kg
Built-in speaker(s) *	✗	Package type	Box
Built-in camera *	✗	Packaging content	
Design		Stand included	✓
Market positioning *	Home	Cables included	HDMI, AC
Product colour *	Black	Manual	✓
Ports & interfaces		Sustainability	
Built-in USB hub *	✗	Sustainability certificates	ENERGY STAR
VGA (D-Sub) ports quantity	1	Other features	
DVI port	✗	Exterior finish type	Textured
HDMI *	✓	Picture enhancement	SmartImage
HDMI ports quantity	1	Recyclable packaging material	100%
Audio input	✗	Regulatory Approvals	UKRAINIAN; CB; TUV Ergo; TUV/GS; CU-EAC; EAEU RoHS; CE Mark
Audio output	✓	Heavy metals free	Hg (mercury)
Ergonomics		EasyRead mode	✓
VESA mounting *	✓	LowBlue mode	✓
Panel mounting interface	100 x 100 mm	Compliance certificates	RoHS
Cable lock slot *	✓	Mean time between failures (MTBF)	50000 h
Cable lock slot type	Kensington	Certification	UKRAINIAN, CB, TUV Ergo, TUV/GS, CU-EAC, EAEU RoHS, CE Mark
Height adjustment *	✗	Logistics data	
Tilt adjustment	✓	Harmonized System (HS) code	85285210
Tilt angle range	-5 - 20°		
On Screen Display (OSD)	✓		



8712581771638

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-MAR-2025. Prints or copies of Information are only valid on the printed Publication date