

Philips V Line 271V8L/00 LED display 68,6 cm (27") 1920 x 1080 Pixel Full HD Nero

Marchio : Philips Famiglia del prodotto: V Line Codice prodotto: 271V8L/00

Nome del prodotto : 271V8L/00

Monitor 271V8L Monitor LCD

Philips V Line 271V8L/00 LED display 68,6 cm (27") 1920 x 1080 Pixel Full HD Nero:

Il monitor Philips V-Line con ampio angolo di visualizzazione offre una visione oltre ogni limite, una qualità elevata e funzioni essenziali. La sincronizzazione adattiva assicura una visualizzazione video fluida. Caratteristiche quali antiriflesso, modalità LowBlue e immagini prive di sfarfallio non affaticano gli occhi.

Philips V Line 271V8L/00. Dimensioni diagonale schermo: 68,6 cm (27"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LED, Superficie display: Opaco, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Montaggio standard VESA. Colore del prodotto: Nero



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display resolution *	1920 x 1080 pixels		
HD type *	Full HD		
Native aspect ratio *	16:9		
Display technology *	LED	Number of OSD languages	21
Panel type *	VA	Plug and Play	✓
Backlight type	W-LED	LED indicators	Operation, Stand-by
Touchscreen *	✗	Power	
Display brightness (typical)	250 cd/m²	Energy efficiency class (SDR) *	E
Response time *	4 ms	Energy consumption (SDR) per 1000 hours *	22 kWh
Display surface	Matt	Power consumption (typical) *	23.3 W
Anti-glare screen	✓	Power consumption (standby) *	0.3 W
Screen shape *	Flat	Power consumption (off)	0.3 W
Aspect ratio	16:9	AC input voltage	100 - 240 V
Contrast ratio (typical) *	3000:1	AC input frequency	50 - 60 Hz
Maximum refresh rate *	75 Hz	Power supply type	Internal
Viewing angle, horizontal	178°	Energy efficiency scale	A to G
Viewing angle, vertical	178°	European Product Registry for Energy Labelling (EPREL) code	400138
Display number of colours *	16.7 million colours	Operational conditions	
Pixel pitch	0.3114 x 0.3114 mm	Operating temperature (T-T)	0 - 40 °C
Pixel density	82 ppi	Storage temperature (T-T)	-20 - 60 °C
Horizontal scan range	30 - 85 kHz	Operating relative humidity (H-H)	20 - 80%
Vertical scan range	48 - 75 Hz	Operating altitude	0 - 3658 m
Viewable size, horizontal	59.8 cm	Non-operating altitude	0 - 12192 m
Viewable size, vertical	33.6 cm	Weight & dimensions	
Digital horizontal frequency	30 - 85 kHz	Width (with stand)	613 mm
Digital vertical frequency	48 - 75 Hz	Depth (with stand)	231 mm
Display diagonal (metric)	68.6 cm	Height (with stand)	456 mm
DDC/CI	✓	Weight (with stand)	3.94 kg
Haze rate	25%		
Surface hardness	3H		
Display sRGB	✓		

Performance			Weight & dimensions	
NVIDIA G-SYNC *	✗		Width (without stand)	613 mm
AMD FreeSync *	✗		Depth (without stand)	45 mm
VESA Adaptive Sync support	✓		Height (without stand)	363 mm
Component video sync		Separate sync, Sync-on-green (SOG)	Weight (without stand)	3.48 kg
Flicker-free technology	✓		Packaging data	
Low Blue Light technology	✓		Package width	730 mm
Multimedia			Package depth	123 mm
Built-in speaker(s) *	✗		Package height	446 mm
Built-in camera *	✗		Package weight	5.53 kg
Design			Package type	Box
Market positioning *		Home	Packaging content	
Product colour *		Black	Stand included	✓
Ports & interfaces			Cables included	HDMI, AC
Built-in USB hub *	✗		Manual	✓
VGA (D-Sub) ports quantity	1		Sustainability	
DVI port	✗		Doesn't contain	Mercury, PVC/BFR
HDMI *	✓		Other features	
HDMI ports quantity	1		Exterior finish type	Textured
Audio output	✓		Picture enhancement	SmartImage
Ergonomics			Recyclable packaging material	100%
VESA mounting *	✓		Regulatory Approvals	UKRAINIAN; CB; TUV Ergo; TUV/GS; CU-EAC; EAEU RoHS; CE Mark
Panel mounting interface		100 x 100 mm	Heavy metals free	Hg (mercury), Pb (lead)
Cable lock slot *	✓		EasyRead mode	✓
Cable lock slot type		Kensington	LowBlue mode	✓
Height adjustment *	✗		Compliance certificates	RoHS
Tilt adjustment	✓		Mean time between failures (MTBF)	50000 h
Tilt angle range	-5 - 20°		Certification	UKRAINIAN, CB, TUV Ergo, TUV/GS, CU-EAC, EAEU RoHS, CE Mark
On Screen Display (OSD)	✓		Logistics data	
			Harmonized System (HS) code	85285210



8712581772062

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-MAR-2025. Prints or copies of Information are only valid on the printed Publication date