


Viewsonic TD2465 visualizzatore di messaggi Pannello piatto interattivo 61 cm (24") LED 250 cd/m² Full HD Nero Touch screen

Marchio : Viewsonic

Codice prodotto: TD2465

Nome del prodotto : TD2465

Viewsonic TD2465. Design del prodotto: Pannello piatto interattivo. Dimensioni diagonale schermo: 61 cm (24"), Tecnologia display: LED, Risoluzione del display: 1920 x 1080 Pixel, Luminosità schermo: 250 cd/m², Tipologia HD: Full HD, Touch screen. Colore del prodotto: Nero



Display		Design	
LED backlight	✓	Product colour *	Black
Display diagonal *	61 cm (24")	VESA mounting *	✓
Display technology *	LED	Panel mounting interface	100 x 100 mm
Display resolution *	1920 x 1080 pixels	Performance	
Display brightness *	250 cd/m ²	Purpose *	Commercial
HD type *	Full HD	Power	
Touchscreen *	✓	Power consumption (typical) *	24 W
Native aspect ratio	16:9	Power consumption (standby) *	0.5 W
Response time	7 ms	Energy efficiency class (SDR)	D
Contrast ratio (typical)	3000:1	Energy consumption (SDR) per 1000 hours	14 kWh
Contrast ratio (dynamic)	20000000:1	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	Energy efficiency scale	A to G
Viewing angle, vertical	178°	Computer system	
Maximum frame rate	60 fps	Built-in processor *	✗
Panel life	30000 h	Weight & dimensions	
Native refresh rate	60 Hz	Display width	550 mm
Surface hardness	7H	Display depth	49 mm
RGB colour space	sRGB	Display height	326 mm
Ports & interfaces		Display weight	4.7 kg
HDMI ports quantity *	1	Width (with stand)	550 mm
HDMI version	1.4	Depth (with stand)	401 mm
DisplayPorts quantity *	1	Height (with stand)	198 mm
USB port *	✓	Weight (with stand)	5.7 kg
USB ports quantity	3	Packaging data	
USB version	3.2 Gen 1 (3.1 Gen 1)	Package width	647 mm
USB connector type	USB Type-A, USB Type-B	Package depth	426 mm
Ethernet LAN *	✗	Package height	138 mm
Wi-Fi *	✗	Package weight	7.2 kg
Audio (L/R) in	1	Packaging content	
Audio (L/R) out	1	Tilt angle	20°
Audio		Tilt adjustment	✓
Built-in speaker(s) *	✓		
Number of built-in speakers	2		
RMS rated power	4 W		

Design		Operational conditions	
Product design *	Interactive flat panel	Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	20 - 90%



0766907017885



766907017885

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.