

Philips Serie 1000 24E2N1100LB/00 Monitor PC 60,5 cm (23.8")  
1920 x 1080 Pixel Full HD LCD Nero

Marchio : Philips

Famiglia del prodotto: Serie 1000


Codice prodotto: 24E2N1100LB/00

Nome del prodotto : 24E2N1100LB/00

Monitor 24E2N1100LB Monitor LCD Full HD

Philips Serie 1000 24E2N1100LB/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Nero:

Questo monitor è ricco di funzioni che consentono di lavorare con assoluta precisione. Grazie alla risoluzione Full HD, alla velocità di aggiornamento di 100 Hz e a un MPRT di 1 ms, questo monitor è in grado di riprodurre immagini estremamente dettagliate e definite. Philips Serie 1000 24E2N1100LB/00. Dimensioni diagonale schermo: 60,5 cm (23.8"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Montaggio standard VESA. Colore del prodotto: Nero



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Cable lock slot type	Kensington
Display resolution *	1920 x 1080 pixels	Height adjustment *	✗
HD type *	Full HD	Tilt adjustment	✓
Native aspect ratio *	16:9	Tilt angle range	-5 - 20°
Display technology *	LCD	On Screen Display (OSD)	✓
Panel type *	VA	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
LED backlight	✓		
Backlight type	W-LED		
Touchscreen *	✗	Number of OSD languages	21
Display brightness (typical)	250 cd/m²	Plug and Play	✓
Response time *	4 ms	LED indicators	Operation, Stand-by
Response time measurement type	GTG (Gray to Gray)	Power	
Response time (MPRT)	1 ms	Energy efficiency class (SDR) *	E
Anti-glare screen	✓	Energy efficiency class (HDR) *	Not available
Screen shape *	Flat	Energy consumption (SDR) per 1000 hours *	18 kWh
Contrast ratio (typical) *	4000:1	Power consumption (typical) *	17.7 W
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power consumption (standby) *	0.5 W
Maximum refresh rate *	100 Hz	Power consumption (off)	0.3 W
Viewing angle, horizontal	178°	AC input voltage	100 - 240 V
Viewing angle, vertical	178°	AC input frequency	50/60 Hz
Display number of colours *	16.7 million colours	Power supply type	External
Pixel pitch	0.2745 x 0.2745 mm	Energy efficiency scale	A to G
Pixel density	92.56 ppi	Operational conditions	
Horizontal scan range	30 - 85 kHz	Operating temperature (T-T)	0 - 40 °C
Vertical scan range	48 - 60 Hz	Storage temperature (T-T)	-20 - 60 °C
Viewable size, horizontal	52.7 cm		
Viewable size, vertical	29.6 cm		
Digital horizontal frequency	30 - 115 kHz		

Display		Operational conditions	
Digital vertical frequency	48 - 100 Hz	Operating relative humidity (H-H)	20 - 80%
Sync-on-green (SOG)	✓	Operating altitude	0 - 3658 m
Display diagonal (metric)	60.5 cm	Non-operating altitude	3658 - 12192 m
DDC/CI	✓	Weight & dimensions	
Haze rate	25%	Width (with stand)	541 mm
Surface hardness	3H	Depth (with stand)	126 mm
Display sRGB	✓	Height (with stand)	378 mm
Performance		Weight (with stand)	2.44 kg
NVIDIA G-SYNC *	✗	Width (without stand)	541 mm
AMD FreeSync *	✗	Depth (without stand)	34 mm
Component video sync	Separate sync, Sync-on-green (SOG)	Height (without stand)	322 mm
Flicker-free technology	✓	Weight (without stand)	2.16 kg
Low Blue Light technology	✓	Packaging data	
Multimedia		Package width	610 mm
Built-in speaker(s) *	✗	Package depth	126 mm
Built-in camera *	✗	Package height	378 mm
Design		Package weight	4.63 kg
Market positioning *	Home	Packaging content	
Product colour *	Black	Cables included	AC, HDMI
Ports & interfaces		Sustainability	
Built-in USB hub *	✗	Doesn't contain	Mercury
VGA (D-Sub) ports quantity	1	Other features	
HDMI *	✓	Exterior finish type	Textured
HDMI ports quantity	1	Picture enhancement	SmartImage
HDMI version	1.4	Recyclable packaging material	100%
HDCP	✓	Regulatory Approvals	CB, CE Mark, TUV/ISO9241-307, TUV-BAUART, EAC, EAEU RoHS, UKCA, EMF, FCC, ICES-003
HDCP version	1.4	Adaptive synchronisation	✓
Ergonomics		EasyRead mode	✓
VESA mounting *	✓	LowBlue mode	✓
Panel mounting interface	100 x 100 mm	Compliance certificates	RoHS
Cable lock slot *	✓	Mean time between failures (MTBF)	50000 h



8721038000351

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-APR-2025. Prints or copies of Information are only valid on the printed Publication date